

DIFFERENTIAL CARRIER

GENERAL SPECIFICATIONS

Front differential carrier

*1: Middle East

*2: High-roof Hardtop

Applied model	Hardtop and High-roof Hardtop						Pick-up			Van and Station Wagon		Canvas Top	
	Light duty model			Heavy duty model			P40 engine	SD33 engine	L28 engine	P40 engine	SD33 and L28 engine	Light duty model	Heavy duty model
	P40 engine	SD33 engine	L28 engine	P40 engine	SD33 engine	L28 engine							
Model	C200												
Type	Cast center												
Ring gear pitch diameter mm (in)	200 (7.87)												
Gear ratio	3.364	4.111	4.375 4.625*2	4.111 3.900*1	4.625		4.111 3.900*1	4.625	4.625 4.875*1	3.900	4.625	3.364	4.111
Number of teeth (Ring gear/Drive gear)	37/11	37/9	35/8 37/8*2	37/9 39/10*1	37/8		37/9 39/10*1	37/8	37/8 39/8*1	39/10	37/8	37/11	37/9
Oil capacity liter (Imp. pt)	1.5 (2-5/8)												

Rear differential carrier

*1: Middle East

*2: High-roof Hardtop

Applied model	Hardtop and High-roof Hardtop						Pick-up			Van and Station Wagon		Canvas Top		
	Light duty model			Heavy duty model			P40 engine	SD33 engine	L28 engine	P40 engine	SD33 and L28 engine	Light duty model	Heavy duty model	
	P40 engine	SD33 engine	L28 engine	P40 engine	SD33 engine	L28 engine								
Model	C200			H233B									C200	H233B
Type	Cast center			Rigid axle suspension									Cast center	Rigid axle suspension
Ring gear pitch diameter mm (in)	200 (7.87)			233 (9.17)									200 (7.87)	233 (9.17)
Gear ratio	3.364	4.111	4.375 4.625*2	4.111 3.900*1	4.625	4.111 3.900*1	4.625	4.625 4.875*1	3.900	4.625	3.364	4.111		
Number of teeth (Ring gear/Drive gear)	37/11	37/9	35/8 37/8*2	37/9 39/10*1	37/8	37/9 39/10*1	37/8	37/8 39/8*1	39/10	37/8	37/11	37/9		
Oil capacity liter (Imp. pt)	1.3 (2-1/4)			2.0 (3-1/2)									1.3 (2-1/4)	2.0 (3-1/2)